



Technical Data Sheet

Issue date: 05/11/2008

Date last modification: 12/04/2018

GRAPHICS - Wide Format Ink Jet Print Media

RIJET 100 MATT WHITE PERMANANT VINYL

Face Material

Matt white monomeric vinyl film.

Type Monomeric vinyl Colour and Finish Matt white

Weight 134 g/m 2 ±10% ISO-536 Thickness 100 μ ±10% ISO 534-80

Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference AP940 permanent Type Acrylic permanent

Min. Appl. Temp.
Service Temp.
Shear
Tack
Final Adhesion

Acrylic permaner
+10°C
-30°C/+120°C
Medium
Medium
Medium N/inch²
High N/inch

<u>Liner</u>

Type One side siliconised clay coated

Kraft

Colour and Finish White

Weight 135 g/m² PP-032 - ISO +10% 536

 $\pm 10\%$ 536
Thickness 145 $\mu \pm 10\%$ ISO 534

Transparency n.a. % DIN 53 147-64

Applications

For advertising and promotional applications (window graphics and outdoor and indoor posters, billboards and signs) and for vehicle applications (flat sided including buses, trams and taxis).

Printing Methods

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following *STORAGE CONDITIONS*:

- • This material must be stored at a temperature of $\,$ 22°C \pm 2°C and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.





