



Xacte 130 130SSRP

Satin Repositionable Polyester Film

Applications

- Wall covering, posters, stickers
- Glass, shop windows, POS
- Furniture customisation

Benefits

- Sticks on almost all smooth or slightly textured surfaces
- Can easily be repositioned several times, perfect stability
- Unique adhesive technology for dry and bubble free application
- Excellent removability up to 6 months on most surfaces
- Antistatic treatment and anti-curl backing liner
- Note: this film should not be applied wet

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.


Printability:



Thickness:



Available widths:



Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

www.kernowcoatings.com | sales@kernowcoatings.com | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitisers Group of Companies