
White Peak KB

Fully coated hard sized folding boxboard with brown kraft back (GC2)

BOARD PROFILE



PRODUCT INFORMATION

- ISO 9001 and ISO 14001 approved supplier.
- All pulp is sourced from well managed and sustainable forests and is fully recyclable. (PEFC and FSC® accredited mill).
- The bleached pulp is ECF.
- Certified for safety with direct contact with dry and non fatty foods (ISEGA).
- Conforms to European standards regarding heavy metal content.nt.

PROCESS SUITABILITY

- Litho
- Gravure
- Screen printing
- Letterpress
- Flexo
- UV and litho varnishing
- Emulsion coating
- Foil and film laminating
- Embossing
- Foil blocking
- Not guaranteed for reverse printing.

TYPICAL USES

- PACKAGING Cartons for frozen, chilled & other food, drinks, household goods, DIY & garden products, toys & games, transit & display outers.
- GRAPHIC Point of sale displays, CD & video sleeves.

SPECIFICATION Mill Makings only.

Microns	g/m2	Stiffness - Taber 15° mN.m	
		MD	CD
280	180	5.5	2.7
315	200	7.8	3.9
365	225	10.6	5.3
400	245	13.3	6.4
432	255	16.0	7.7
457	265	19.3	9.3
508	285	24.5	11.8
533	295	26.3	12.5
559	312	31.3	14.9
610	330	38.3	18.3
660	345	43.9	20.6
711**	370	52.2	24.5
Tolerance +/-5%	+/-5%	-10%	-10%

Smoothness (PPS) $1.0\mu m$ +/- 0.5 Brightness (TAPPI) 81% +/- 2 (top)

Cobb Value Top (1min) 25-45gsm, Back (2min) 50-80gsm.

Indent mill makings are available in all the thicknesses listed above

The above information is given for general guidance only and is subject to change without notice.



^{**} Produced on special request