

eTEC Mount Film

Product Description

Premium Mounting Tape For the permanent, self-adhesive lamination of even surfaces. Very well processible, provides excellent adhesion to almost all materials like plastics, films, wood, glasses or metals with excellent flatness. Suitable for in- and outdoor application. The product then can be used over a long period of time internally for mounting in galleries, museums and for photography. The film/adhesive combination will not materially affect the image or photograph, due to its pH neutral adhesive (other interferences between ink and photopaper to be checked separately).

Key Features

- 12µm, transparent PET film
- 90 g/m² white release paper, special coating
- pure polyacrylic, permanent, transparent, pH neutral, Solvent free adhesive
- Adhesive weight 60 g/m²
- Total Thickness 0.07 mm

Additional Information

Adhesion on steel: (after 20 min) 8N/25mm AFERA 5001

Adhesion on steel: (after 24 h) 11N/25mm AFERA 5001

Application temperature: min. +10°C

End-Use Temperature range: from -40°C to +80°C

Shelf life: 2 years (see application information)

Durability: 2 years

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme conditions (tropical climate, high humidity, high UV-light exposure or polluted areas) can decrease the durability in a dramatically way

All values and information issues are approximate and should only be used as a guideline. Products should be tested by the end user for absolute suitability with the substrates and environments upon which it is intended to be used. Premier Paper cannot be held responsible for any damage to printing and finishing equipment or surfaces to which products are applied.