

eTEC WV300FR Matt White

Product Description

eTEC WV300 FR matt white is a 100micron smooth matt white monomeric PVC film with a high tack grey adhesive and class 0 Fire rating suitable for using on demanding wall surfaces.

Key Features

- 100 micron Film thickness +/- 5
- 140gsm PE clay coated silicon kraft paper liner
- Grey Adhesive provides excellent Opacity
- Hi Grab Adhesive performs superbly on challenging surfaces
- BS 476 Class 0 Fire Rated
- Great printability across range of printing technologies
- Short to Medium term indoor and outdoor applications (flat surfaces)
- Durability: 4 years indoor & 3 years outdoor
- Can also be used for low energy surfaces e.g. Polypropylene, ABS etc

Printability

Solvent, Eco Solvent, Latex & UV

Additional Information

Peel strength >22N / 25mm (after 24hrs on stainless steel)

Ensure the surface to be applied to is clean and free from dirt and debris.

Although WV300 is suitable for challenging surfaces, some surfaces should be avoided like: Heavy textured porous surfaces, application onto wallpapers, chalking powdery surfaces, latex and Matt paints. If in doubt a test should be carried out to ensure suitability.

When using Solvent and Eco-solvent inks, lay product flat after printing for at least 24 hours to 'solvent outgas'.

How to store: To prolong the product's usable life, avoid excessive exposure to UV radiation, store unused wall Print On in a dry place and do not expose to extreme temperatures (temp. 23° +/- 2°C, R.H. 55%).

Shelf life: 3 years (in advised storage conditions).

All values and information issues are approximate and should only be used as a guideline. Products should be tested by the end user for absolute suitability with the substrates and environments upon which it is intended to be used. Premier Paper cannot be held responsible for any damage to printing and finishing equipment or surfaces to which products are applied.